



FIG. 1






2/42












FIG. 7A

object_definition_segment
segment_type
segment_length
object_id
object_version_number
last in sequence flag
object_data_fragment
COMPRESSED GRAPHICS
OBJECT

FIG. 7B








FIG. 10




FIG. 11








FIG. 12















FIG. 17


OBJECT BUFFER





```
FIG. 18 PTS( DSn[PCS)] >=DTS( DSn[PCS] )+DECODEDURATION( DSn )
        DECODEDURATION( DSn ) is calculated as follows:
    decode_duration = 0:
    decode_duration += PLANEINITIALIZATIONTIME( DSn );
    if( DSn. PCS. num_of_objects == 2)
        decode_duration += WAIT( DSn, DSn. PCS. OBJ[0], decode_duration );
        if( DSn. PCS. OBJ[0]. window_id == DSn. PCS. OBJ[1]. window_id )
                decode_duration += WAIT( DSn, DSn. PCS. OBJ[1], decode_duration );
                decode_duration += 90000*(SIZE(DSn. PCS. OBJ[0]. window_id)//256*10^6);
        else
                decode_duration += 90000*( SIZE( DSn. PCS. OBJ[0]. window_id )//256*106);
                decode_duration += WAIT( DSn, DSn. PCS. OBJ[1], decode_duration );
                decode_duration += 90000*(SIZE(DSn. PCS. OBJ[1]. window_id)//256*10^6);
    else if( DSn. PCS. num_of_objects == 1 )
       decode_duration += WAIT( DSn, DSn. PCS. OBJ[0], decode_duration );
       decode_duration += 90000*(SIZE(DSn. PCS. OBJ[0]. window_id)//256*10^6);
    return decode_duration;
       PLANEINITIALIZATIONTIME( DSn ) is calculated as follows:
   initialize duration=0:
   if( DSn. PCS. composition_state= = EPOCH_START )
      initialize_duration = 90000*( 8*video_width*video_height//256*106);
   else
       for (i=0; i < WDS. num_windows: i++)
              if( EMPTY(DSn.WDS.WIN[i],DSn ) )
                     initialize_duration += 90000*(SIZE(DSn. WDS. WIN[i])//256*10^6);
   return initialize_duration:
       WAIT( DSn, OBJ, current_duration ) is calculated as follows:
   wait_duration = 0:
   if( EXISTS( OBJ. object_is, DSn ) )
       object_definition_ready_time = PTS( GET( OBJ. object_id. DSn ) );
      current_time = DTS( DSn. PCS )+current_duration;
      if( current_time < object_definition_ready_time )
              wait_duration += object_definition_ready_time - current_time );
   return wait duration:
                                   18/42
```












FIG. 21A










23/42












WO 2004/098193





WO 2004/098193






30/42








Segment_type =Normal Case END **DS20** PCS END NORMAL REPRODUCTION WDS PDS ODS FIG. 33 Segment_type =Acquision Point **DS10** PCS END ODS PDS DS1 Segment_type =Epoch Start WDS PCS 33/42

PCS END END **DS20** ~ rd3 CODED DATA BUFFER OF REPRODUCING APPARATUS END GNORE DS AND NOT LOADING DS10 PDS ODS FIG. 34 PCS | WDS \sim rd2 END END ODS DS1 PDS PCS |WDS | PDS | ODS PCS | WDS DS1 MEMORY LOAD












38/42







41/42

WO 2004/098193

